



These racks may can be modified from 4-loops to 3-, 2-, and 1-loop configurations.

MATERIAL: SEE NOTES
FINISH: REMOVE WELD SPATTER; BLACK POWDER COAT
QUANTITY: 1

<small>DEPT CODE</small> SSFA <small>STAINLESS FABRICATION</small>	 <small>THIRD ANGLE PROJECTION</small>
<small>FABRICATION TOLERANCE = ± 1/8"</small> <small>PRESSBRAKE TOLERANCE</small> <small>UNDER 1/4" THK = ± 1/16"</small> <small>1/4" THK AND OVER = ± 1/8"</small> <small>BEND ACCURACY = ± 2°</small> <small>BEND RADIUS = 1.1 x METAL THICKNESS</small> <small>STANDARD SHOP TOLERANCES (UNLESS OTHERWISE SPECIFIED)</small>	

115 DRY RIVER ROAD
 BRIDGEWATER, VA 22812
 www.shickel.com

DISCLOSURES AND CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF SHICKEL CORPORATION. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SHICKEL CORPORATION IS PROHIBITED.

TITLE: SAMPLE BIKE RACK					
JOB: XXXXX					
CUSTOMER: XXXXX					
DETAILED BY: WJK	DATE: 10/30/14	JOB NUMBER: XXXXXX-XXX	DWG SIZE: B	SCALE: 1:12	
CHECKED BY:	DATE:	PROJECT MANAGER: XXXXX	SHEET: 1 OF 1	REV:	
PART NUMBER:		DRAWING NAME:			